

## 21003791 - Tandem 30.100 EV Wire mesh tray L3m



## **Product data**

Product code:	21003791
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972000124
Technical description:	Tandem 30.100 EV Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

## **Technical data**

Width:	100
Model:	Without connector
Height:	30
Surface protection:	Galvanic/electrolytic zinc plated
Weight:	0.526
Length:	3000
Material:	Steel
Integrated partition:	None
Usable cross section:	2634
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Working length:	3000
RAL-number:	-
Working temperature:	-20 - 120
Diameter longitudinal wire:	3.9



Diameter transverse wire:	3.9
Safe working load according to IEC 61537 with support spacing 2.0 m:	80
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Possible support spacing:	
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	120
Safe working load according to IEC 61537 with support spacing 2.5 m:	50
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-