


# 22004793 - Tandem 54.150 HDG Wire mesh tray L3m



## Product data

|                        |                                      |
|------------------------|--------------------------------------|
| Product code:          | 22004793                             |
| Brand:                 | Niedax Group                         |
| Series:                | Gouda Wire Mesh                      |
| Type:                  | Tandem                               |
| EAN Code:              | 08719972000551                       |
| Technical description: | Tandem 54.150 HDG Wire mesh tray L3m |
| ETIM class:            | EC000853 - Mesh cable tray           |

## Technical data

|   |       |
|---|-------|
| Possible support spacing:   | - - - |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 150   |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -     |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -     |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 300   |

|   |                    |
|---|--------------------|
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 200                |
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -                  |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -                  |
| Width:  | 150                |
| Model:  | Without connector  |
| Height:   | 55                 |
| Surface protection:   | Hot-dip galvanised |
| Weight:   | 0.995              |
| Material quality:   | Other              |
| Length:   | 3000               |
| Material:   | Steel              |
| Integrated partition:   | None               |
| Usable cross section:   | 7665               |
| Profile shape:  | U-shape            |
| Suitable for circuit integrity:                                       | No                 |
| Load test type according to IEC 61537:                                | Type III           |
| Operating temperature:  | -20 - 120          |
| Diameter longitudinal wire:   | 3.9                |
| Diameter transverse wire:   | 3.9                |
| RAL-number:   | -                  |
| Working length:   | 3000               |