


## 22004796 - Tandem 54.150 SS316 Wire mesh tray L3m



## **Product data**

| Product code:          | 22004796                               |
|------------------------|--|
| Brand:                 | Niedax Group                           |
| Series:                | Gouda Wire Mesh                        |
| Туре:                  | Tandem                                 |
| EAN Code:              | 08719972000575                         |
| Technical description: | Tandem 54.150 SS316 Wire mesh tray L3m |
| ETIM class:            | EC000853 - Mesh cable tray             |

## **Technical data**

| er:   |
|---|
| ngth: 3000  |
| ransverse wire: 3.9   |
| emperature: -20 - 120   |
| ongitudinal wire: 3.9   |
| pport spacing:  |
| ng load according to IEC 61537<br>ort spacing 0.5 m:  |
| ng load according to IEC 61537<br>ort spacing 1.0 m:  |
| ng load according to IEC 61537<br>ort spacing 1.5 m:  |
| ng load according to IEC 61537<br>ort spacing 2.5 m:  |
| ng load according to IEC 61537<br>ort spacing 3.0 m:  |
| repport spacing:  Ing load according to IEC 61537  Ing load according to IEC 61537 |



| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -                            |
|---|------------------------------|
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -                            |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -                            |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -                            |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -                            |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 200                          |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                            |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -                            |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -                            |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -                            |
| Width:  | 150                          |
| Model:  | Without connector            |
| Height:   | 55                           |
| Surface protection:   | Other                        |
| Weight:   | 0.92                         |
| Material quality:   | Stainless steel 316 (1.4401) |
| Length:   | 3000                         |
| Material:   | Stainless steel              |
| Integrated partition:   | None                         |
| Usable cross section:   | 7665                         |
| Profile shape:  | U-shape                      |
| Suitable for circuit integrity:                                       | No                           |
| Load test type according to IEC 61537:                                | Type III                     |
|   |                              |