


22009794 - Tandem 54.500 SS304 Wire mesh tray L3m



Product data

Product code:	22009794
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972000728
Technical description:	Tandem 54.500 SS304 Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

Technical data

Width:	500
Model:	Without connector
Height:	54
Surface protection:	Other
Weight:	2.958
Material quality:	Stainless steel 304 (1.4301)
Length:	3000
Material:	Stainless steel
Integrated partition:	None
Usable cross section:	25438
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Safe working load according to IEC 61537 with support spacing 2.0 m:	600

Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	800
Safe working load according to IEC 61537 with support spacing 2.5 m:	400
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Working temperature:	-20 - 120
Diameter longitudinal wire:	4.82
RAL-number:	-
Working length:	3000
Diameter transverse wire:	5.82