


# 23008791 - Tandem 105.400 EV Wire mesh tray L3m



## Product data

Product code:	23008791
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972001183
Technical description:	Tandem 105.400 EV Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

## Technical data

Width:	400
Model:	Without connector
Height:	105
Surface protection:	Galvanic/electrolytic zinc plated
Weight:	3.314
Material quality:	Other
Length:	3000
Material:	Steel
Integrated partition:	None
Usable cross section:	40072
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
RAL-number:	-
Working length:	3000
Diameter longitudinal wire:	6

Diameter transverse wire:	6
Working temperature:	-20 - 120
Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	1200
Safe working load according to IEC 61537 with support spacing 2.5 m:	700
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.0 m:	900
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Type of connection:	Screwed