

23009794 - Tandem 105.500 SS304 Wire mesh tray L3m



Product data

Product code:	23009794
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Туре:	Tandem
EAN Code:	08719972001244
Technical description:	Tandem 105.500 SS304 Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

Technical data

RAL-number:	-
Working length:	3000
Operating temperature:	-20 - 120
Diameter longitudinal wire:	6
Diameter transverse wire:	6
Possible support spacing:	
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	1200
Safe working load according to IEC 61537 with support spacing 2.5 m:	700
Safe working load according to IEC 61537 with support spacing 3.0 m:	-



	Godda Holland
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.0 m:	900
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Type of connection:	Screwed
Width:	500
Model:	Without connector
Height:	105
Surface protection:	Other
Weight:	3.401
Material quality:	Stainless steel 304 (1.4301)
Length:	3000
Material:	Stainless steel
Integrated partition:	None
Usable cross section:	50026
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Load test type according to IEC 61537:	Type III