

23009796 - Tandem 105.500 SS316 Wire mesh tray L3m



Product data

Product code:	23009796
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Туре:	Tandem
EAN Code:	08719972001251
Technical description:	Tandem 105.500 SS316 Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

Technical data

Width:	500
Model:	Without connector
Height:	105
Surface protection:	Other
Weight:	3.401
Material quality:	Stainless steel 316 (1.4401)
Length:	3000
Material:	Stainless steel
Integrated partition:	None
Usable cross section:	50026
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Safe working load according to IEC 61537 with support spacing 0.5 m:	-



Safe working load according to IEC 61537 with support spacing 2.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 6.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Operating temperature: Operating temperature: Each of 1530 with support spacing 12.0 m: Can be support spa		
with support spacing 2.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 6.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: - 20 - 120 Diameter longitudinal wire: 6 Diameter transverse wire:	3	1200
with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 6.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: -20 - 120 Diameter longitudinal wire: 6 Diameter transverse wire:		900
with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 6.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6 Diameter transverse wire: 6		-
with support spacing 6.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: - 20 - 120 Diameter longitudinal wire: 6 Diameter transverse wire:		-
with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6 Diameter transverse wire: 6		-
with support spacing 8.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6 Diameter transverse wire: 6		-
with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6 Diameter transverse wire:	•	-
with support spacing 9.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6	3	-
Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire: 6		-
with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: 6 Diameter transverse wire:	Possible support spacing:	
with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire:		-
with support spacing 5.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire:		700
with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire:		-
with support spacing 12.0 m: RAL-number: Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire:		-
Working length: Operating temperature: Diameter longitudinal wire: Diameter transverse wire: 3000 -20 - 120 6 Diameter transverse wire: 6	9	-
Operating temperature: -20 - 120 Diameter longitudinal wire: 6 Diameter transverse wire: 6	RAL-number:	-
Diameter longitudinal wire: Diameter transverse wire: 6	Working length:	3000
Diameter transverse wire: 6	Operating temperature:	-20 - 120
	Diameter longitudinal wire:	6
The section of the se	Diameter transverse wire:	6
Type of connection: Screwed	Type of connection:	Screwed