


# 23010796 - Tandem 105.600 SS316 Wire mesh tray L3m



## Product data

|                        |   |
|------------------------|---|
| Product code:          | 23010796                                |
| Brand:                 | Niedax Group                            |
| Series:                | Gouda Wire Mesh                         |
| Type:                  | Tandem                                  |
| EAN Code:              | 08719972001299                          |
| Technical description: | Tandem 105.600 SS316 Wire mesh tray L3m |
| ETIM class:            | EC000853 - Mesh cable tray              |

## Technical data

|  |                              |
|--|------------------------------|
| Width:                                 | 600                          |
| Model:                                 | Without connector            |
| Height:                                | 105                          |
| Surface protection:                    | Other                        |
| Weight:                                | 3.844                        |
| Material quality:                      | Stainless steel 316 (1.4401) |
| Length:                                | 3000                         |
| Material:                              | Stainless steel              |
| Integrated partition:                  | None                         |
| Usable cross section:                  | 60044                        |
| Profile shape:                         | U-shape                      |
| Suitable for circuit integrity:        | No                           |
| Load test type according to IEC 61537: | Type III                     |
| RAL-number:                            | -                            |
| Operating temperature:                 | -20 - 120                    |

|   |         |
|---|---------|
| Working length:   | 3000    |
| Diameter longitudinal wire:   | 6       |
| Diameter transverse wire:   | 6       |
| Possible support spacing:   | - - -   |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 1200    |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 700     |
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 900     |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -       |
| Type of connection:   | Screwed |