

## 26000233 - SLB MK 30.75 HDG Marine ladder L3m



### Product data

|                        |                                    |
|------------------------|------------------------------------|
| Product code:          | 26000233                           |
| Brand:                 | Niedax Group                       |
| Series:                | Gouda Marine ladders               |
| Type:                  | SLB                                |
| EAN Code:              | 08719972002890                     |
| Technical description: | SLB MK 30.75 HDG Marine ladder L3m |
| ETIM class:            | EC000854 - Cable ladder            |

### Technical data

|                                 |                    |
|---------------------------------|--------------------|
| Working length:                 | 3000               |
| Working temperature:            | -20 - 120          |
| Vertical cable ladder:          | -                  |
| Width:                          | 75                 |
| Height:                         | 30                 |
| RAL-number:                     | -                  |
| Surface protection:             | Hot-dip galvanised |
| Weight:                         | 3.067              |
| Type of rung:                   | Flat profile       |
| Side perforation:               | No                 |
| Material quality:               | Other              |
| Length:                         | 3000               |
| Material:                       | Steel              |
| Usable cross section:           | -                  |
| Type of side joist:             | Flat profile       |
| Suitable for circuit integrity: | No                 |
| Rung centre spacing:            | 250                |

|                                                                       |        |
|-----------------------------------------------------------------------|--------|
| Fixation rung:                                                        | Welded |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -      |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -      |
| Possible support spacing:                                             | - - 3  |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -      |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -      |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -      |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -      |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -      |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -      |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -      |