

# 31042153 - Tray GP 28.75 HDG Cable tray L3m

## Product data

|                        |                                  |
|------------------------|----------------------------------|
| Product code:          | 31042153                         |
| Brand:                 | Niedax Group                     |
| Series:                | Gouda Cable duct                 |
| Type:                  | Tray                             |
| EAN Code:              | 08719972008427                   |
| Technical description: | Tray GP 28.75 HDG Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray            |

## Technical data

|  |                    |
|--|--------------------|
| Width:   | 75                 |
| Model:   | Without connector  |
| Height:  | 27                 |
| RAL-number:  | -                  |
| Surface protection:  | Hot-dip galvanised |
| Weight:  | -                  |
| Material thickness:  | 1.5                |
| Side perforation:  | Yes                |
| Material quality:  | Other              |
| Length:  | 3000               |
| Material:  | Steel              |
| Bottom perforation:  | Yes                |
| Usable cross section:  | 1836               |
| NATO-mounting holes:   | No                 |
| Suitable for circuit integrity:                                      | No                 |
| With cover:  | No                 |
| Safe working load according to IEC 61537 with support spacing 2.0 m: | 175                |
| Safe working load according to IEC 61537 with support spacing 3.0 m: | 25                 |
| Safe working load according to IEC 61537 with support spacing 4.0 m: | -                  |

|   |           |
|---|-----------|
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -         |
| Possible support spacing:   | - - 3     |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 450       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 300       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 80        |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -         |
| Type of connection:   | Screwed   |
| Working temperature:  | -20 - 120 |
| Working length:   | 3000      |