

## 31045154 - Tray GP 28.200 SS304 Cable tray L3m

### Product data

Product code:	31045154
Brand:	Niedax Group
Series:	Gouda Cable duct
Type:	Tray
EAN Code:	08719972008588
Technical description:	Tray GP 28.200 SS304 Cable tray L3m
ETIM class:	EC000047 - Cable tray

### Technical data

Width:	200
Model:	Without connector
Height:	27
RAL-number:	-
Surface protection:	Untreated
Weight:	-
Material thickness:	1
Side perforation:	Yes
Material quality:	Stainless steel 304 (V2A)
Length:	3000
Material:	Stainless steel
Bottom perforation:	Yes
Usable cross section:	5148
NATO-mounting holes:	No
Suitable for circuit integrity:	No
With cover:	No
Safe working load according to IEC 61537 with support spacing 2.0 m:	175
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-

Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Possible support spacing:	- - 3
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	450
Safe working load according to IEC 61537 with support spacing 1.5 m:	300
Safe working load according to IEC 61537 with support spacing 2.5 m:	80
Safe working load according to IEC 61537 with support spacing 3.0 m:	25
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Operating temperature:	-20 - 120
Type of connector:	Screwed
Working length:	3000