

31062142 - Tray ZP 28.75 PG Cable tray L3m

Product data

Product code:	31062142
Brand:	Niedax Group
Series:	Gouda Cable duct
Type:	Tray
EAN Code:	08719972008762
Technical description:	Tray ZP 28.75 PG Cable tray L3m
ETIM class:	EC000047 - Cable tray

Technical data

Type of connector: Operating temperature: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.0 m:	Working length:	3000
Safe working load according to IEC 61537 with support spacing 2.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450	Type of connector:	Screwed
with support spacing 2.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450	Operating temperature:	-20 - 120
with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450		175
with support spacing 4.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450	3	25
with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450		-
with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450		-
with support spacing 12.0 m: Possible support spacing: Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450		-
Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450	3	-
with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: 450	Possible support spacing:	3
with support spacing 1.0 m:		-
Safe working load according to IEC 61537	_	450
with support spacing 1.5 m:	Safe working load according to IEC 61537 with support spacing 1.5 m:	300
Safe working load according to IEC 61537 with support spacing 2.5 m:	3	80



Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Width:	75
Model:	Without connector
Height:	27
RAL-number:	-
Surface protection:	Continuously galvanised
Weight:	-
Material thickness:	1
Side perforation:	No
Material quality:	Other
Length:	3000
Material:	Steel
Bottom perforation:	No
Usable cross section:	1898
NATO-mounting holes:	No
Suitable for circuit integrity:	No
With cover:	No