

## 31062142 - Tray ZP 28.75 PG Cable tray L3m

## **Product data**

| Product code:          | 31062142                        |
|------------------------|---------------------------------|
| Brand:                 | Niedax Group                    |
| Series:                | Gouda Cable duct                |
| Type:                  | Tray                            |
| EAN Code:              | 08719972008762                  |
| Technical description: | Tray ZP 28.75 PG Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray           |

## **Technical data**

| 75                      |
|-------------------------|
| Without connector       |
| 27                      |
| -                       |
| Continuously galvanised |
|                         |
| 1                       |
| No                      |
| Other                   |
| 3000                    |
| Steel                   |
| No                      |
| 1898                    |
| No                      |
| No                      |
| No                      |
| 175                     |
| 25                      |
| -                       |
|                         |



| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -         |
|---|-----------|
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -         |
| Possible support spacing:   | 3         |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 450       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 300       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 80        |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -         |
| Working length:   | 3000      |
| Connector design:   | Screwed   |
| Working temperature:  | -20 - 120 |
|   |           |