# 31066148 - Tray ZP 28.250 C Cable tray L3m

## Product data

| | |
|---|---|
| Product code: | 31066148 |
| Brand: | Niedax Group |
| Series: | Gouda Cable duct |
| Type: | Tray |
| EAN Code: | 08719972009004 |
| Technical description: | Tray ZP 28.250 C Cable tray L3m |
| ETIM class: | EC000047 - Cable tray |

## Technical data

| | |
|---|---|
| Colour: | Other |
| Width: | 250 |
| Model: | Without connector |
| Height: | 27 |
| Type of connection: | Screwed |
| RAL-number: | - |
| Surface protection: | Continuously galvanised and coated |
| Weight: | - |
| Material thickness: | 1 |
| Side perforation: | No |
| Material quality: | Other |
| Length: | 3000 |
| Working temperature: | -20 - 120 |
| Material: | Steel |
| Bottom perforation: | No |
| Usable cross section: | 6448 |
| NATO-mounting holes: | No |
| Working length: | 3000 |
| Suitable for circuit integrity: | No |
| With cover: | No |
| Possible support spacing: | - - 3 |
| Safe working load according to IEC 61537 with support spacing 0.5 m: | - |

| | |
|---|---|
| Safe working load according to IEC 61537 with support spacing 1.0 m: | 450 |
| Safe working load according to IEC 61537 with support spacing 1.5 m: | 300 |
| Safe working load according to IEC 61537 with support spacing 2.0 m: | 175 |
| Safe working load according to IEC 61537 with support spacing 2.5 m: | 80 |
| Safe working load according to IEC 61537 with support spacing 3.0 m: | 25 |
| Safe working load according to IEC 61537 with support spacing 4.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 5.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 6.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 7.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 8.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 9.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | - |