

## 31067148 - Tray ZP 28.300 C Cable tray L3m

### Product data

|                        |                                 |
|------------------------|---------------------------------|
| Product code:          | 31067148                        |
| Brand:                 | Niedax Group                    |
| Series:                | Gouda Cable duct                |
| Type:                  | Tray                            |
| EAN Code:              | 08719972009059                  |
| Technical description: | Tray ZP 28.300 C Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray           |

### Technical data

|  |                                    |
|--|------------------------------------|
| Colour:  | Other                              |
| Width:   | 300                                |
| Model:   | Without connector                  |
| Height:  | 27                                 |
| RAL-number:  | -                                  |
| Surface protection:  | Continuously galvanised and coated |
| Weight:  | -                                  |
| Material thickness:  | 1                                  |
| Side perforation:  | No                                 |
| Material quality:  | Other                              |
| Length:  | 3000                               |
| Material:  | Steel                              |
| Bottom perforation:  | No                                 |
| Usable cross section:  | 7748                               |
| NATO-mounting holes:   | No                                 |
| Suitable for circuit integrity:                                      | No                                 |
| With cover:  | No                                 |
| Working temperature:   | -20 - 120                          |
| Working length:  | 3000                               |
| Possible support spacing:  | - - 3                              |
| Safe working load according to IEC 61537 with support spacing 1.0 m: | 450                                |

|   |         |
|---|---------|
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 80      |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 300     |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 175     |
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | 25      |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -       |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -       |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -       |
| Type of connection:   | Screwed |