

# 31083154 - Tray GPR 28.100 SS304 Cable tray L3m



## Product data

|                        |                                      |
|------------------------|--------------------------------------|
| Product code:          | 31083154                             |
| Brand:                 | Niedax Group                         |
| Series:                | Gouda Cable duct                     |
| Type:                  | Tray                                 |
| EAN Code:              | 08719972009189                       |
| Technical description: | Tray GPR 28.100 SS304 Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray                |

## Technical data

|   |           |
|---|-----------|
| Working temperature:  | -20 - 120 |
| Working length:   | 3000      |
| Possible support spacing:   | - - 3     |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 600       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 410       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 160       |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 250       |

|   |                           |
|---|---------------------------|
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | 50                        |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -                         |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -                         |
| Type of connection:   | Screwed                   |
| Width:  | 100                       |
| Model:  | Without connector         |
| Height:   | 28                        |
| RAL-number:   | -                         |
| Surface protection:   | Untreated                 |
| Weight:   | -                         |
| Material thickness:   | 1                         |
| Side perforation:   | Yes                       |
| Material quality:   | Stainless steel 304 (V2A) |
| Length:   | 3000                      |
| Material:   | Stainless steel           |
| Bottom perforation:   | Yes                       |
| Usable cross section:   | 2254                      |
| NATO-mounting holes:  | No                        |
| Suitable for circuit integrity:                                       | No                        |
| With cover:   | No                        |