

31084156 - Tray GPR 28.150 SS316 Cable tray L3m



Product data

Product code:	31084156
Brand:	Niedax Group
Series:	Gouda Cable duct
Type:	Tray
EAN Code:	08719972009240
Technical description:	Tray GPR 28.150 SS316 Cable tray L3m
ETIM class:	EC000047 - Cable tray

Technical data

Possible support spacing:	3
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	600
Safe working load according to IEC 61537 with support spacing 1.5 m:	410
Safe working load according to IEC 61537 with support spacing 2.0 m:	250
Safe working load according to IEC 61537 with support spacing 3.0 m:	50
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-



Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.5 m:	160
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Width:	150
Model:	Without connector
Height:	28
RAL-number:	-
Surface protection:	Untreated
Weight:	-
Material thickness:	1
Side perforation:	Yes
Material quality:	Stainless steel 316 (V4A)
Length:	3000
Material:	Stainless steel
Bottom perforation:	Yes
Usable cross section:	3404
NATO-mounting holes:	No
Suitable for circuit integrity:	No
With cover:	No
Type of connector:	Screwed
Operating temperature:	-20 - 120
Working length:	3000