

31104142 - Tray ZPR 28.150 PG Cable tray L3m



Product data

Product code:	31104142
Brand:	Niedax Group
Series:	Gouda Cable duct
Туре:	Tray
EAN Code:	08719972009561
Technical description:	Tray ZPR 28.150 PG Cable tray L3m
ETIM class:	EC000047 - Cable tray

Technical data

Width:	150
Model:	Without connector
Height:	28
RAL-number:	<u>-</u>
Surface protection:	Continuously galvanised
Weight:	-
Material thickness:	1
Side perforation:	No
Material quality:	Other
Length:	3000
Material:	Steel
Bottom perforation:	No
Usable cross section:	3404
NATO-mounting holes:	No
Suitable for circuit integrity:	No



With cover: Possible support spacing: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 2.0 m:	
Safe working load according to IEC 61537 with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537	
with support spacing 0.5 m: Safe working load according to IEC 61537 with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 250	
with support spacing 1.0 m: Safe working load according to IEC 61537 with support spacing 1.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 according to IEC 61537 Safe working load according to IEC 61537 according to IEC 61537 Safe working load according to IEC 61537	
with support spacing 1.5 m: Safe working load according to IEC 61537 with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 according	
with support spacing 2.5 m: Safe working load according to IEC 61537 with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 Safe working load according to IEC 61537	
with support spacing 3.0 m: Safe working load according to IEC 61537 with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537	
with support spacing 7.0 m: Safe working load according to IEC 61537 with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537	
with support spacing 10.0 m: Safe working load according to IEC 61537 with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537	
with support spacing 9.0 m: Safe working load according to IEC 61537 with support spacing 11.0 m: Safe working load according to IEC 61537 250	
with support spacing 11.0 m: Safe working load according to IEC 61537 250	
/50	
Safe working load according to IEC 61537 with support spacing 4.0 m:	
Safe working load according to IEC 61537 with support spacing 5.0 m:	
Safe working load according to IEC 61537 with support spacing 6.0 m:	
Safe working load according to IEC 61537 with support spacing 8.0 m:	
Safe working load according to IEC 61537 with support spacing 12.0 m:	
Connector design: Screwed	
Working temperature: -20 - 120	
Working length: 3000	