

## 31107144 - Tray ZPR 28.300 SS304 Cable tray L3m



## **Product data**

| Product code:          | 31107144                             |
|------------------------|--------------------------------------|
| Brand:                 | Niedax Group                         |
| Series:                | Gouda Cable duct                     |
| Туре:                  | Tray                                 |
| EAN Code:              | 08719972009738                       |
| Technical description: | Tray ZPR 28.300 SS304 Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray                |
|                        |                                      |

## **Technical data**

| Operating temperature:   | -20 - 120 |
|--|-----------|
| Type of connector:   | Screwed   |
| Working length:  | 3000      |
| Possible support spacing:  | 3         |
| Safe working load according to IEC 61537 with support spacing 0.5 m: | -         |
| Safe working load according to IEC 61537 with support spacing 1.0 m: | 600       |
| Safe working load according to IEC 61537 with support spacing 1.5 m: | 410       |
| Safe working load according to IEC 61537 with support spacing 2.5 m: | 160       |
| Safe working load according to IEC 61537 with support spacing 3.0 m: | 50        |
| Safe working load according to IEC 61537 with support spacing 7.0 m: | -         |



| Safe working load according to IEC 61537 with support spacing 10.0 m: | -                         |
|---|---------------------------|
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -                         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -                         |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 250                       |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -                         |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -                         |
| Width:  | 300                       |
| Model:  | Without connector         |
| Height:   | 28                        |
| RAL-number:   | -                         |
| Surface protection:   | Untreated                 |
| Weight:   | -                         |
| Material thickness:   | 1                         |
| Side perforation:   | No                        |
| Material quality:   | Stainless steel 304 (V2A) |
| Length:   | 3000                      |
| Material:   | Stainless steel           |
| Bottom perforation:   | No                        |
| Usable cross section:   | 6854                      |
| NATO-mounting holes:  | No                        |
| Suitable for circuit integrity:                                       | No                        |
| With cover:   | No                        |