

# 40024112 - Unic 100.800 PG Cable Ladder c.t.c.100 L3m



## Product data

Product code:	40024112
Brand:	Niedax Group
Series:	Gouda Cable ladder
Type:	Unic
EAN Code:	08719972050556
Technical description:	Unic 100.800 PG Cable Ladder c.t.c.100 L3m
ETIM class:	EC000854 - Cable ladder

## Technical data

Width:	800
Height:	100
RAL-number:	-
Surface protection:	Continuously galvanised
Weight:	7.084
Type of rung:	Imperforated profile
Side perforation:	Yes
Material quality:	Other
Length:	3000
Material:	Steel
Usable cross section:	58018
Type of side joist:	Profile (open)
Suitable for circuit integrity:	No
Rung centre spacing:	100
Fixation rung:	Other
Possible support spacing:	- - 3

Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.5 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	3000
Safe working load according to IEC 61537 with support spacing 2.0 m:	1800
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Working temperature:	-20 - 120
Working length:	3000
Vertical cable ladder:	-