

40034112 - Unic 100.300 PG Cable Ladder c.t.c.50 L3m

Product data

| Product code: | 40034112 |
|------------------------|---|
| Brand: | Niedax Group |
| Series: | Gouda Cable ladder |
| Туре: | Unic |
| EAN Code: | 08719972050709 |
| Technical description: | Unic 100.300 PG Cable Ladder c.t.c.50 L3m |
| ETIM class: | EC000854 - Cable ladder |

Technical data

| Operating temperature: | -20 - 120 |
|--|-------------------------|
| Working length: | 3000 |
| Vertical cable ladder: | - |
| Width: | 300 |
| Height: | 100 |
| RAL-number: | - |
| Surface protection: | Continuously galvanised |
| Weight: | 5.037 |
| Type of rung: | Imperforated profile |
| Side perforation: | Yes |
| Material quality: | Other |
| Length: | 3000 |
| Material: | Steel |
| Usable cross section: | 28918 |
| Type of side joist: | Profile (open) |
| Suitable for circuit integrity: | No |
| Rung centre spacing: | 50 |
| Fixation rung: | Other |
| Safe working load according to IEC 61537 with support spacing 2.0 m: | 1800 |



| Safe working load according to IEC 61537 with support spacing 4.0 m: | - |
|---|------|
| Safe working load according to IEC 61537 with support spacing 5.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 7.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | - |
| Possible support spacing: | 3 |
| Safe working load according to IEC 61537 with support spacing 0.5 m: | - |
| Safe working load according to IEC 61537 with support spacing 1.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 1.5 m: | 3350 |
| Safe working load according to IEC 61537 with support spacing 2.5 m: | 1100 |
| Safe working load according to IEC 61537 with support spacing 3.0 m: | 750 |
| Safe working load according to IEC 61537 with support spacing 6.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 8.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 9.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | - |
| | |